

Environmental Solutions for the Construction and Mining Industry



ILMEG Products AB develops, manufactures, markets and sells environmental solutions for the construction and mining industry.

The hydraulically powered Dust Collector product range. A complete range of hydraulically driven dust collectors mainly for the rock drilling industry for hole sizes up to 203 mm (8")



ECON 900 H Hydraulically powered dust collector

system to be used on rock drills drilling up to 51 mm (2") holes.



HS 900 Hydraulically powered dust collector system to be used on rock drills drilling up to 76 mm (3") holes.



X-100 Hydraulically powered dust collector system to be used on rock drills drilling up to 100 mm (4") holes.



X-125

Hydraulically powered dust collector system to be used on rock drills drilling up to 127 mm (5") holes.



X-150

Hydraulically powered dust collector system to be used on rock drills drilling up to 165 mm (6 1/2") holes.



X-200 Hydraulically powered dust collector system to be used on rock drills drilling up to 203 mm (8") holes.

Hydraulic Dust Collectors									
Туре	Max hole dimension mm	Oil flow requirement I/min	Hydraulic pressure Bar	Approx. dimensions WxDxH mm	Approx. weight Kg				
ECON 900H	51	25	100	510x458x1230	140				
HS 900	76	25	170	620x590x1745	180				
X-100	100	22	200	740x957x1062	160				
X-125	127	22	200	740x957x1062	160				
X-150	165	44	200	1078x897x1133	220				
X-200	203	80	200	1263x1065x1133	350				



The fully pneumatically powered Dust Collector product range. A complete range of fully pneumatic dust collectors mainly for the rock drilling industry for hole sizes up to 140 mm $(5 \frac{1}{2})$



MICRO

Fully pneumatic dust collector system to be used together with one hand-held rock drill hand-held breakers or light rig mounted rock drills



MACRO

Fully pneumatic dust collector system to be used together with two handheld rock drills, two hand-held breakers or two light rig mounted rock drills



ECON 900 Fully pneumatic dust collector system to be used on pneumatic rock drills drilling up to 76 mm (3") holes.



AS 900

Fully pneumatic dust collector system to be used on pneumatic rock drills drilling up to 105 mm (4") holes HIDDINES HOLK

AM 900

Fully pneumatic dust collector system to be used on pneumatic rock drills drilling up to 140 mm (5 $\frac{1}{2}$) holes.

Pneumatic Dust Collectors									
	Max hole dimension	Filter area	Air consumption	Air pressure	Approx. dimensions	Approx. weight			
Туре	mm	m ²	m ³ /min	Bar	WxDxH mm	Kg			
MICRO	38	1,6	1,2	7	300x335x880	30			
MACRO	2 x 38	3,6	1,7	7	362x458x1230	45			
ECON 900	76	7,2	1,9	7	570x440x1420	110			
AS 900	105	10,8	3,3	7	570x650x1530	145			
AM 900	140	19,2	4,5	7	830x790x1565	190			

Accessories for the rock drilling industry:



MEC-ANGIE Precision drilling instruments







Pre Separators

Pick-up hoods

BHS 100 Bag Handling System






CDC 2000

The CDC 2000 is an electrically powered dust collector system for extreme environmental requirements with regards to dust. For instance in underground mining and construction, construction in residential areas, construction close to hospitals and in quarries in residential areas. The system has been designed to suction dust from the pick-up-hood housing, through the dust collector to finally be dumped in a sealed container.

A virtually dust free process.



HAC 2000


The ILMEG HAC 2000 dust control system is used on asphalt milling machines to improve the working conditions with regards to dust control. The system consists of a specially-designed hydraulically driven fan and customized suction devices. The fan is made of wear-resistant material for long service life. To facilitate ready access to the system, the fan can easily be opened for service and cleaning if necessary.

The suction devices are applied at the point of dust production, connected to the suction fan with a suction hose and the fan then conveys the dust to the milling machine conveyor.



AFC 2000

Asphalt fume control system improves the working condition and protects the environment in the asphalt paving industry.



Bvba GEOTECHNO SprI - Edmond Vandervaerenstraat 60A 1560 Hoeilaart België - Belgique Tel: 00.32(0)2.657.61.77 - Fax: 00.32(0)2.657.54.58 - web : <u>www.geotechno.be</u> - e-mail : <u>info@geotechno.be</u>